QB-30/ QB-30LED **Fashion Home** Aquarium







- Up to 14 Lighting Combinations
- Turn up top cover, Convenient for landscape and maintenance.
- Internal filter. Filtration, oxygen supplying and water circulation are integrated together, easy to maintain.
- Polyhedral & symmetrical, no difference between front and rear side, universal placement for more visions.







Specifications

	Model		QB-30		QB-30LED			
	Capacity		30L					
	Voltage		DC12V					
ı	Style		LED lamp					
	Color		Black White		Red			
	Lighting	Power			7W			
		Color	E	Blue White				
	Filtration	Model		BT200B				
		Power	3W					
		Qmax	200L/h					
	Size ((mm)	320×320×320	320×320×320				

Using Schematic Diagram



R Series **Fashionable Aquariums**



HAILEA 海利





Product description

• Top cover with two small covers, Convenient to feed and maintain.







Using Schematic Diagram





Specifications

Specifications								
Mo	del	R-20	R-20 R-35		R-50			
Capa	acity	20L	2	5L	45L			
Voltage Style		DC12V						
		LED lamp						
Col	lor	E	Black W	hite F	Red			
Lighting	Power	3W	3	W	4W			
Lighting	Color		Blue	White				
	Model	BT200B						
Filtration	Power	3W						
	Qmax	200L/h						
Size (mm)		317×230×340	377×277×386		452×317×450			

HK Series Chillers







- Microcomputer control system for the convenience of user.
- High efficiency and energy saving. Water temperature will fall down quickly and economically.
- Adopts Freon-free R134a refrigerating system, which is safe and environment friendly.
- Anti-corrosive pure titanium evaporator for fresh & sea water dual use.
- Temperature memory system that makes the chiller refrigerate continuously according to the previous temperature when the power is supplied again to protect the animals and plants in the aquarium.






convenience of user.



Contains full set of fittings, easy to install.



Solid chassis along with overall stylish housing design ensure chiller blend well with the surrounding working environment.



Specifications

	Power	Voltage	Frequency	Voltage	Frequency	Water Refrigerated	Iced Medium	Rate of Flow	Weight	Size
Model		110-120V	60Hz	220-240V	50Hz					
		Working Current		Working Current						
HK-150A	1/10HP	2.2A		1.	1A	150L		800-1500L/h	13kg	430×255×380mm
HK-300A	1/4HP	4.7A		1.8A		300L	R134a	1500-3000L/h	18.6kg	457×330×430mm
HK-500A	1/2HP	5.4A		2.4A		500L		2500-5000L/h	19.3kg	480×355×480mm
HK-1000A	1/2HP	1/2HP 10.2A		3.	2A	1000L	R22	5000-10000L/h	19.8kg	560×380×480mm

