



ALL INDIA DISTRIBUTORS  
**AQUASSTAR**  
 NO:5, WEST MADA STREET, KOLATHUR, CHENNAI-600099.

## 紫外线杀菌灯 UV-C CLARIFYING

ALGAE CONTROL IN  
 ECONOMIC WAY



外观精致



性能好



密封佳



承力强



型号/Model	CUV-107	CUV-109A	CUV-111	CUV-111A	CUV-118	CUV-136	CUV-155	CUV-172
功耗/Power Consumption(w)	11	12	15	15	20	40	58	80
紫外线灯管功率/UV-C(w)	7	9	11	11	18	36	55	2x36
灯管寿命/UV-C(%)8000hours	85	85	85	85	85	85	85	85
适用水量/Capacity(l)	6000	8000	10000	10000	20000	35000	50000	60000
最大压力/Max Pressure(bar)	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
最大流量/Through Flow(l/h)	1200	1500	1700	1700	2500	4500	5000	6000
接口尺寸/Inlet&outlet Adapter	1/2"	3/2"-1 1/2"	3/2"-1 1/2"	1/2"-1 1/2"	3/4"-1 1/2"	3/4"-1 1/2"	3/4"-1 1/2"	3/4"-1 1/2"
电线长度/Cable Length	1m/2m	1m/2m	1m/4m	1m/2m	1m/4m	1m/4m	1m/4m	2x1m/4m
长度Length(mm)	236	270	314	340	314	490	672	980

**紫外线杀菌灯 ALGAE CONTROL IN ECONOMIC WAY**  
**UV-C CLARIFYING**



**HIGH EFFICIENCY**

■ CUV-209



■ CUV-207



■ CUV-209A



■ CUV-211



■ CUV-211A



■ CUV-218/224



■ CUV-236



■ CUV-272



型号/Model	CUV-207	CUV-209	CUV-209A	CUV-211	CUV-211A	CUV-218	CUV-224	CUV-236	CUV-272
功耗/Power Consumption(w)	11	12	12	15	15	20	24	40	80
紫外线灯管功率/UV-C(w)	7	9	9	11	11	18	24	36	2x36
灯管寿命/UV-C(%)8000hours	85	85	85	85	85	85	85	85	85
适用水量/Capacity(l)	6000	8000	8000	12000	12000	20000	35000	45000	60000
最大压力/Max Pressure(bar)	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
最大流量/Through Flow(l/h)	1200	1500	1500	1700	1700	2500	4500	6000	6000
接口尺寸/Inlet&outlet Adapter	1/2" - 3/4"	3/2" - 1 1/2"	1/2" - 1 1/2"	3/4" - 1 1/2"	3/4" - 1 1/2"	3/4" - 1 1/2"	3/4" - 1 1/2"	3/4" - 1 1/2"	3/4" - 1 1/2"
电线长度/Cable Length	3m	5m	3m	5m	3m	5m	5m	5m	2x5m
长度Length(mm)	242	276	290	323	360	460	460	518	980



ALL INDIA DISTRIBUTORS

**AQUASSTAR**

NO:5, WEST MADA STREET, KOLATHUR, CHENNAI-600099.

## 紫外线杀菌灯 UV-C CLARIFYING



■ CUV-528



外观精致



性能好



密封佳



安装简



■ CUV-655

## STRONG UVC WITH AMERICAN TECHNOLOGY MAGNETIC VIBRATION



### FEATURES

1. These UV-C devices keep your pond clean and your fish healthy.
2. Stainless steel interior reflects the UV-C radiation, which increases efficiency by up to 30%. Furthermore, this stainless steel interior protects the plastic body against the UV-C radiation.
3. These UV-C devices (including the case) are with earth connection, which is more safe.
4. With special connection design, these UV-C devices can be worked in maximum 10 meters under water pressure.
5. CUV-5 devices are with Preheat uv germicidal lamp(4-pins SE);  
CUV-6 devices are with H-shaped uv germicidal lamps;

型号/Model	CUV-515	CUV-528	CUV-540	CUV-618	CUV-624	CUV-636	CUV-655	CUV-695
紫外线灯管功率/UV-C(W)	15	28	40	18	24	36	55	95
灯管寿命/UV-C(%) hours	8000	8000	8000	8000	8000	8000	8000	8000
适用水量/Capacity(L)	25000	45000	60000	25000	40000	55000	65000	80000
最大压力/Max Pressure(bar)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
最大流量/Through Flow(L/h)	3000	5000	7000	3000	5000	7000	8000	8000
接口尺寸/Inlet & Outlet Adapter	1-2"	1-2"	1-2"	1-2"	1-2"	1-2"	1-2"	1-2"
电线长度/Cable Length	5m	5m	5m	5m	5m	5m	5m	5m